

Feature

- 1. COG with SMT
- 2. 5.0 V single power supply (Typ.)
- 3. 5x7 dots with cursor
- 4. Built-in controller: Compatible with HD44780/ST7066U
- 5. Color: White/Yellow
- 6. Support MCU interfaces:
 - 4 / 8-bit 6800 series parallel interface (STD)
 - I²C interface (Option)
- 7. Operating temperatures:-40℃ to 80℃
- 8. 4 sets of CGROM (hardware selectable)
 - ENGLISH/JAPANESE
 - ENGLISH/CYRILLIC
 - ENGLISH/EUROPEAN I
 - ENGLISH/EUROPEAN II



Mechanical Data

Item	Standard Value	Unit
Module Dimension	98.0 x 60.0	mm
Active Area	70.42 x 20.82	mm
Dot Size	0.55 x 0.55	mm
Character Size	2.95 x 4.75	mm

Electronic Characteristics

Item	Symbol	Condition	Typical Value	Unit
Input Voltage	Vdd	Vdd=+5.0V	5.0	V
Supply Current	Idd	Vdd=+5.0V	40.0	mA
Life Time(White)		80cd/m ²	70K	hrs
Life Time(Yellow)		80cd/m ²	100K	hrs

Pin Assignment

Pin	Symbol	Level	Description
1	GND	0V	Ground
2	VDD	5.0V	Supply voltage for logic.
3	NC	-	-
4	RS	H/L	H:DATA , L:Instruction code
5	R/W	H/L	H:Read(MPU←Module) L:Write(MPU→Module)
6	E	H→L	Chip enable signal
7-14	DB0~7	H/L	Data bit 0~7
15	NC	-	-
16	NC	-	-

Dimension

