

UJ Light Technologies

Feature

- 1. OLED display 128 x 64 dots
- 2. Built-in controller SPD0301
- 3. +3.3V power supply
- 4. 1/64 duty cycle
- 5. Color: white or yellow
- 6. Option: 6800, SPI, I2C interface

Mechanical Data

| Item | Standard Value | Unit |
|------------------|--------------------|------|
| Module Dimension | 75.0 x 52.7 | mm |
| Viewing Area | 60.0 x 30.0 | mm |
| Dot Size | 0.40×0.40 | mm |
| Dot Pitch | 0.43×0.43 | mm |
| | | |

!"#\$%&'()+*?123 4567890;: a/,.AB CDEFGHIJKLMNOPQ RSTUUWXYZ!_[]{}

Pin Assignment

| Pin | Symbol | Level | Function | |
|------|-------------|----------|---|--|
| 1 | Vdd | 3.3V | Supply voltage for logic | |
| 2 | Vss | 0V | Grond | |
| 3 | NC | | No connection | |
| 4-11 | DB0-7 | H/L | Data bus line | |
| 12 | CS | H/L | Chip select pin | |
| 13 | NC | | No connection | |
| 14 | /RES | H/L | Hardware Reset pin | |
| 15 | WR | H/L | Data write enable pin | |
| 16 | RS | H/L | H: Data, L: Command | |
| 17 | RD | H/L | Data read enable pin | |
| 18 | NC | | No connection | |
| 19 | DISF VCC | H/L H | DISF: VCC Voltage ON/OFF VCC: Supply Voltage for OLED | |
| 20 | NC | | No connection | |

Electronic Characteristics

| Item | Symbol | Condition | Value | Unit |
|------------------|--------|-------------|------------|--------|
| Input Voltage | Vdd | Vdd = +3.3V | 3.3 (Typ.) | V |
| Supply Current | ldd | Vdd = +3.3V | 220 (Max.) | mA |
| Pixel Brightness | Lu | Vdd = +3.3V | 70 | cd /m² |

^{*} Contrast setting:0Xa0,Color: white ,Pixel all on

Dimension

