

Feature

- 1. SMT PCB with metal frame
- 2. Built-in controller UCi6963c or equivalent
- 3. +5V single power supply
- 4. 1/128 duty cycle
- 5. Option: LED backlight
- 6. Option: negative voltage



Mechanical Data

Item	Standard Value	Unit
Module Dimension	129.0 x 102.0	mm
Viewing Area	101.0 x 82.0	mm
Dot Size	0.54 x 0.54	mm
Dot Pitch	0.58 x 0.58	mm

Pin Assignment

Pin	Symbol	Function
1	FGND	Frame ground
2	Vss	Logic power supply(GND)
3	Vdd	Logic power supply (+5V)
4	Vadj	Contrast Adjustment
5	Vee	Negative voltage output (-16V)
6	/WR	Data write
7	/RD	Data read
8	/CE	Chip enable
9	C/D	Command/Data read/write
10	/HALT	Clock halt signal
11	/RST	Reset LCD module signal
12~19	DB0~7	Data bus line
20	NC	No connection

Electronic Characteristics

Item	Symbol	Condition	Typical Value	Unit
Input Voltage	Vdd	Vdd = +5V	5.0	V
Supply Current	Idd	Vdd = +5V	42	mA
LCD Driving Voltage	Vdd-Vadj	25°C	18.9	V
LED Forward Voltage	Vf	25°C	4.2	V
LED Forward Current	If	25°C	650	mA

Dimension

